

Appendix 1

Product Description and/or Approval Condition

Certificate No : RTD03790-AE002

Date of Issue : 1st April, 2019

A. Product Description

1. Product Specification

Basic Model No.	J5015E J5015PT2	J5023E J5023PT2	J5025E J5025PT2	J5040E J5040PT2	J5050E J5050PT2
Connection size [mm]	15 15	25 25	25 25	40 40	50 50
Capacity [liter/min]	* 37.5 ** 50	37.5 50	120 160	187.5 250	375 500
Temperature [°C]			-10 ~ 125 -10 ~ 150(Hall)		

* : Maximum(continuous), ** : Maximum(discontinuous, 8 hrs/day)

2. Approved Drawings and Documents

- 1) Drawings
0801-3202 Rev.E, 0801-3227 Rev.B, 0801-3228 Rev.B, 0801-3229 Rev.-,
0801-3302 Rev.A, 0801-3304 Rev.-, 0801-3306 Rev.A, 0801-3308 Rev.A,
0801-3310 Rev.A

3. Test Reports, etc.

- 1) 13C00863RPT01 (2013.08.06), 16C00664RPT01 (2016.06.15),
17C01021RPT01 (2017.10.02), M17.001-P17.001 (2017.08.31)

B. Approval Condition

1. Application & Limitation

- 1) This approval is granted on the basis of the test reports and approved documentation.
- 2) Degree of protection shall be compiled with Rule Pt.6 Ch.1 Sec.2 201.2.(5).

2. Individual Product Cert. and Drawing Approval Requirement

- 1) Individual Product Certification is not required.

3. Marking

- 1) The product or packing is to be marked with the manufacturer's name and type designation on a suitable position.

4. Others

- 1) Test condition

Test	Condition	Remark
EMC	All locations including the bridge and deck zone	-
Temperature	+5 ~ +70°C	-
Vibration	Acceleration 0.7g	-

< End of certificate >